

Technical data



Technical
data

Stage V



**Technical data on the Park Ranger 2150
- basic machine and attachments**



Technical specifications

Basic machine

Length	mm	2225
Width	mm	1015
Height with / without cabin	mm	1935 / 1210
Weight with / without cabin ¹⁾	kg	670 / 560
Payload	kg	630 / 740
Gross vehicle weight (GVA)	kg	1300
Turning circle - kerb to kerb	mm	3000
Turning circle - inside	mm	1100
Engine: Perkins diesel 403J-11	hp / kW	26 / 19
4 wheel drive		std.

¹⁾ Includes: 75 kg operator and 90% fuel capacity.



Optimize your park maintenance

- with one machine and 19 dedicated functions

The Park Ranger 2150 is the most attractive choice within the compact machine class. With tailor-made quality attachments, fully aligned with the machine, you have 19 dedicated machines in one.

With compact dimensions and great manoeuvrability you have easy access to narrow areas and places and versatile handling of all ground care and winter assignments as well as the suction/sweeper jobs.

With the powerful 26 hp Stage V Perkins engine and 4 wheel drive you always have the needed power and traction needed for your tasks. Furthermore, you have a utility machine which lives up to the emission standards of the future.

Top performance in every aspect

Egholm makes no compromises in quality. All attachments are carefully designed to supply the optimum performance in its specific area. High quality materials and functional couplings, ensures professional results and durable performance.

All attachments can be changed by one person in less than 4 minutes - no tools needed to shift, and no heavy lifting involved ! You can, therefore, easily use the machine for different tasks during the day without wasting time on attachment changes in the workshop. And we all know: time is money. Easy handling is key both for operation efficiency and for safety.

For Park Ranger 2150 the following attachments are available:

Sweeping

- Suction sweeper

Ground care

- Weed brush
- Rotary, mulch or collection mower 1000
- Rotary or mulch mower 1200
- Rotary or mulch mower 1500
- Grass collector
- Hedge cutter
- Flail mower / verticutter
- Lawn edger
- Environmental rake
- Leaf suction unit
- Tipping shovel
- Tipper trailer
- Load carrier with tip


Winter

- Snow sweeper
- Snow blower
- Snow plough
- Snow V-plough
- Salt and sand spreader



Basic machine

- Park Ranger 2150



Standard equipment:

Drive	Hydraulic drive. Pure hydraulic-driven utility machine only requiring minimal maintenance.
Hydraulics	The oil type is Rando HDZ 68, tank capacity is 15 l. Working pressure of up to 180 bar.
Lights and mirrors	For machines with cabin EU standard driving lights are placed at the top of the cabin and side mirrors at the side of the cabin. Machines without cabin are fitted with stop and indicator lights at the back of the machine.
12-volt socket	For mobile phone charger.
Coupling	TÜV approved (acc. ECE R55).

Extra equipment (options):

Radio	Bluetooth radio with USB port and SD slot or DAB+ radio with Bluetooth. Headset included.
Large radiator cover	Fit your Park Ranger 2150 with the large radiator cover when cutting grass, as the cover protects the engine against overheating.
Load carrier	A practical little load carrier that provides room to transport hand tools.
Shovel and broom holder	A little smart option that provides room to bring a shovel and a broom on the machine.
Anti-corrosion treatment	The anti corrosion treatment of the basic machine is recommended when operating in the winter season.

Technical specifications


Dimensions		
Length	mm	2225
Width	mm	1015
Height with / without cabin	mm	1935 / 1210
Weights & other data		
Weight with / without cabin ¹⁾	kg	670 / 560
Payload with / without cabin	kg	630 / 740
Gross vehicle weight	kg	1300
Allowed axle load, front	kg	740
Allowed axle load, back	kg	740
Max. permitted trailer weight without brakes	kg	750
Max. combined weight without brakes	kg	2050
Max. permitted trailer weight with brakes	kg	1500
Max. combined weight with brakes	kg	2800
Performance		
Turning circle - kerb to kerb	mm	3000
Turning circle - inside	mm	1100
Operating speed, max.	km/h	16
Noise level		
Passing (Outside - 2009/63/EC)	dB(A)	N/A
Operators seat (Inside - 2009/76/EC)	dB(A)	N/A
Engine		
Model	Perkins diesel 403J-11	
EU norm	Stage V	
Engine power	hp/kW	26 / 19
Fuel tank capacity	l	20
Fuel consumption at 2400 rpm (EN 15429-2)	l/h	2,8
Fuel consumption at 3400 rpm (EN 15429-2)	l/h	4,6
CE certified according to EU directive		

¹⁾ Includes: 75 kg operator and 90% fuel capacity.



Suction sweeper

- Park Ranger 2150



Standard equipment:

Self-cleaning filter system	As standard the hopper has a rotation filter system and a fresh water tank with 100 l capacity.
Hopper stand	Frame for easy fitting, removal and storage of the hopper.
Height regulation	Nose wheel for height regulation of the front brushes for excellent sweeping result and minimal brush wear.
Speed adjustment	Adjustable speed of the front brushes is standard.

Extra equipment (options):

External wander hose	The external vacuum hose is ideal for cleaning hard-to-reach places such as between parked bicycles or in stairwells. The 6 m hose is stored on top of the hopper and is always ready to use.
Third side brush	Extends the sweeping width to 1660 mm. This brush is operated hydraulically, which makes it perfect for sweeping right up to house walls or under benches, for example.

Technical specifications

Dimensions		
Length	mm	2900
Width	mm	1200
Height with / without cabin	mm	1935 / 1850
Height with remote wander hose	mm	2200
Storage dimensions		
Length	mm	1350
Width	mm	1010
Height	mm	1920
Weights		
Weight with / without cabin ¹⁾	kg	960 / 850
Payload with / without cabin	kg	340 / 450
Weight - hopper	kg	135
Weight - front brushes, 2 brushes	kg	68
Weight - 3 rd brush	kg	23
Hopper		
Hopper net volume (EN 15429-1)	l	438
Hopper gross volume	l	458
Hopper load, max.	kg	300
Tipping height	mm	1300
Fresh water tank capacity	l	100
Sweeping system & performance		
Working width - 2 brushes	mm	1220
Working width up to - 3 rd brush	mm	1660
Turning circle - 2 brushes and hopper (wall to wall) (EN 15429-1)	mm	3240
Brush speed	rpm	0-140
Brush diameter Ø	mm	570
Suction tube diameter Ø	mm	150
Ground clearance below suction mouth	mm	55
Ground clearance below brushes	mm	140
Noise level - outside LwA (2000/14/EC)	dB(A)	107
Dust levels: EU-norm PM10 and PM2.5		****
CE certified according to EU directive		

¹⁾ Includes: hopper, 2 brushes, 75 kg operator and 90% fuel capacity.



Weed brush

- Park Ranger 2150



Standard equipment:

- Hydraulic adjustable brush** The flexible brush is controlled by the hydraulic system of the machine.
- Brush regulator** The brush regulator allows you to adjust the brush speed.
- Guard** The guard prevents weeds from spreading over a wide area and for collecting the weeds under the vacuum nozzle.

Extra equipment (options):

- Vacuum nozzle and hopper** A dedicated vacuum nozzle with a integrated brush cylinder makes it possible to combine the weed brush with the suction sweeper hopper allowing you to vacuum the uprooted weeds into the hopper immediately.



Technical specifications

Dimensions		
Length	mm	3300
Width	mm	1230
Height with / without cabin	mm	1935 / 1850
Storage dimensions		
Length	mm	1450
Width	mm	900
Height	mm	630
Weight		
Weight (weed brush)	kg	85
Performance		
Working width	mm	700
Brush speed	rpm	0-114
Brush diameter Ø	mm	700
Ground clearance below suction mouth (option)	mm	30
Ground clearance below brush	mm	160
Operating speed	km/h	2-4
CE certified according to EU directive		



Rotary/mulch mower 1000

- Park Ranger 2150



Standard equipment:

Tilting for cleaning The mower can tilt up and rest on two support wheels making cleaning easy.

Extra equipment (options):

Large radiator cover To avoid choking of the radiator grille while mowing dry grass in dusty surroundings, the large radiator cover can be fitted.

Mulch mower kit The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.

Collection mower (kit) Rebuild the rotary mover to a collection mower. Collecting the grass trimmings ensures the most professional looking result and healthiest lawn. It is recommended to use the dedicated grass collector for this purpose. Please see separate data sheet for this attachment.

Technical specifications

Dimensions

Length	mm	2700
Width	mm	1100
Height with / without cabin	mm	1935 / 1210

Storage dimensions

Length	mm	880
Width	mm	1100
Height	mm	480

Weight

Weight (rotary mower)	kg	90
-----------------------	----	----

Performance

Ground clearance below mower	mm	80
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1050
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m ² /h	10500
Theoretical mowing area - collection / mulch	m ² /h	8400

Max. recommended operating speed

Rotary mower *	km/h	10
Collection mower *	km/h	8-10
Mulch mower (shorter grass) *	km/h	10
* Depends on grass and height		

Noise level


Noise level - outside LwA (2000/14/EC)	dB(A)	105
--	-------	-----

CE certified according to EU directive



Rotary/mulch mower 1200

- Park Ranger 2150



Standard equipment:

Tilting for cleaning The mower can tilt up and rest on two support wheels making cleaning easy.

Extra equipment (options):

Large radiator cover Choking of the radiator grille while mowing very dry grass in dusty surroundings can be avoided by mounting the large radiator cover.

Mulch mower kit The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.

Technical specifications

Dimensions		
Length	mm	2780
Width	mm	1290
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	980
Width	mm	1290
Height	mm	480
Weight		
Weight (rotary mower)	kg	103
Performance		
Ground clearance below mower	mm	110
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1210
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m ² /h	15600
Theoretical mowing area - mulch	m ² /h	12000
Max. recommended operating speed		
Rotary mower *	km/h	10
Mulch mower (shorter grass) *	km/h	10
* Depends on grass and height		
Noise level		
Noise level - outside LwA (2000/14/EC)	dB(A)	105
CE certified according to EU directive		



Rotary/mulch mower 1500

- Park Ranger 2150



Standard equipment:

Hydraulic tipping function	Using the control handle, the cutter can be tipped into vertical position for easy cleaning and maintenance of the cutter.
Hydraulic height adjustment	The cutting height is adjustable using the hydraulic system of the machine.
Specially developed blades	The cutter is equipped with specially developed blades which ensure a nice result in shorter time and using less power.
Support wheels	When the cutter is disassembled from the machine, it can be tipped to rest on two support wheels for easier transportation and storage.
Piano wheels	Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in their wheel forks for durability.
Lawn protection screens	The lawn protection screens protect both the blades and the lawn. The screens prevent larger sharp or hard objects from hitting the knives, thereby reducing wear of the knives. The screens also protect the lawn, as you avoid them running down into the lawn if the mower is lowered too much.

Extra equipment (options):

Large radiator cover	Choking of the radiator grille while mowing very dry grass in dusty surroundings can be avoided by mounting the large radiator cover.
Mulch mower kit	The rotary mower can be changed into a mulch mower with a new set of blades and a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.

Technical specifications

Dimensions		
Length	mm	2800
Width	mm	1582
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	990
Width	mm	1582
Height	mm	480
Weight		
Weight (rotary mower)	kg	127
Performance		
Ground clearance below mower	mm	95-115
No. of mower blades	pcs.	3
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1500
Adjustable cutting height	mm	30-80
Theoretical mowing area - rotary	m ² /h	15000
Theoretical mowing area - mulch	m ² /h	13500
Max. recommended operating speed		
Rotary mower *	km/h	10
Mulch mower (shorter grass) *	km/h	9
* Depends on grass and height		
Noise level		
Noise level - outside LwA (2000/14/EC)	dB(A)	N/A
CE certified according to EU directive		



Grass collector

- Park Ranger 2150



1100 mm



3100 mm

1950 mm

Standard equipment:

- Hydraulic tipping** Easy emptying of the hopper without leaving the cabin. Hydraulic tipping function and automatic lid opening. With a tipping height of 1800 mm it can be emptied directly into a container.
- Two-piece suction hose** The two-piece suction hose ensures easy access in case of clogging.
- Air intake** A special air intake on both sides of the hopper protects the engine of the utility machine against grass dust.
- Safety valve** A safety valve makes sure to stop both turbine and rotary mower while the hopper is being emptied.
- Stand** A stand for easy and quick attaching/detaching of the hopper is standard equipment.

Extra equipment (options):

- Mulch and rotary mower kits** You can quickly convert the grass collector to a non-collecting mulch mower or standard rotary mower with the help of special kits available.
- Leaf suction unit** The grass collector can also be combined with the leaf suction unit for easy collection of leaves.

Technical specifications

Dimensions		
Length (with mower 1000)	mm	3100
Width (with mower 1000)	mm	1100
Height with cabin	mm	1950
Storage dimensions		
Length	mm	1700
Width	mm	1050
Height	mm	2000
Weights		
Weight with / without cabin ¹⁾	kg	995 / 885
Payload with / without cabin	kg	305 / 415
Weight (grass collector)	kg	170
Weight (frame)	kg	31
Hopper (grass collector)		
Hopper volume	l	470
Hopper load, max.	kg	120
Tipping level from ground, with high tipping	mm	1800
Performance		
Airflow	m³/h	1500
Airspeed	km/h	70
Max. recommended operating speed	km/h	8-10
Noise level		
Noise level - outside LwA (2000/14/EC)	dB(A)	105
CE certified according to EU directive		

¹⁾ Includes: grass collector, mower 1000, 75 kg operator and 90% fuel capacity.



Hedge cutter

- Park Ranger 2150



Standard equipment:

- Protective guard** For mounting on the cutter bar during transport and storage.
- Support strut** The hedge cutter is equipped with support strut which are used when dismounting the tool for secure parking.
- Holder** To always have spray oil to hand, a holder for spray oil is mounted on the vertical boom.

Technical specifications



Dimensions		
Length	mm	3500
Width	mm	1700
Height with / without cabin	mm	1935 / 1450
Storage dimensions		
Length	mm	1000
Width	mm	1500
Height	mm	1650
Weights		
Weight (cutter)	kg	25
Weight (arm)	kg	105
Performance		
Cutting width	mm	1300
Cutting height, max. *	mm	3200
Horizontal cutting height *	mm	0-2100
Horizontal reach *	mm	0-2500
Branch thickness, max.	mm	25
Operating speed	km/h	0-2
No. of blades	pcs.	36
Oil consumption	l/min.	25
CE certified according to EU directive		

* The cutting boom range is stated with mounted cutter bar.



Flail mower

- Park Ranger 2150



Standard equipment:

Clearing height adjustment

The clearing height is adjusted using the two forward wheels (rough and fine adjustment). Rough adjustment using seven adjusting rings in interval 0-110 mm. Fine adjusting carried out by a variable-adjustable lever.

Extra equipment (options):

Verticutter knives

Changing the flails with vertical blades converts the flail mower into a verticutter, which deals with moss and weeds without the need for pesticides. The verticutter removes moss while simultaneously cutting a thin score in the turf, so the grassroots are aired. This strengthens the grass so the turf is much more resilient to weeds.

Counterweight

It is recommend to use a counterweight on the back of the Park Ranger 2150 when using the flail mower. (2 x 18,5 kg)

Radiator cover

It is recommend to use a radiator cover for mowing in very dry grass and dusty surroundings, as this stops the radiator from becoming choked with grass and protects the motor.


Technical specifications

Dimensions		
Length	mm	2895
Width	mm	1475
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	955
Width	mm	1475
Height	mm	435
Weight		
Weight (flail mower / verticutter)	kg	154 / 151
Performance		
No. of flails	pcs.	76
No. of vertical blades (max.)	pcs.	38
Flail - clearing width	mm	1226
Flail - clearing height	mm	1-110
Rotation of blades	rpm	2800
Verticutter - clearing width	mm	1172
Verticutter - clearing depth	mm	0-15
CE certified according to EU directive		



Lawn edger

- Park Ranger 2150



1200-1350 mm



2270 mm

1210 mm
1935 mm

Standard equipment:

- Rotary cutter with two blades** The lawn edger has two blades for optimal performance. While cutting the edge the machine also cultivates the ground for a perfect result.
- Adjustable working depth** The working depth is regulated according to ground conditions, by adjusting the support wheel.
- Reversible blade** Makes it possible to cutting outwards or inwards.
- Adjustable offset** Opens up the possibilities of cultivating soil.

Technical specifications

Dimensions		
Length	mm	2270
Width	mm	1200-1350
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	540
Width	mm	920
Height	mm	500
Weight		
Weight (lawn edger)	kg	53
Performance		
Ground clearance height under cutter	mm	140
Cutting depth (max.)	mm	95
Offset	mm	150
Operating speed	km/h	1-2
CE certified according to EU directive		



Environmental rake

- Park Ranger 2150



1100 mm



2500 mm

1210 mm
1935 mm

Standard equipment:

Rear facing draw hoes The environmental rake has rear facing draw hoes which does not catch on roots.

Extra equipment (options):

Rear lifter A mandatory option to lift and lower the rake.



Technical specifications

Dimensions		
Length	mm	2500
Width	mm	1100
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	500
Width	mm	1100
Height	mm	260
Weight		
Weight (environmental rake)	kg	32
Performance		
Working width	mm	1100
Ground clearance below rake	mm	80
Working depth of the drag hoes	mm	20-40
CE certified according to EU directive		



Leaf suction unit

- Park Ranger 2150



Standard equipment:

- Leaf collection hose** The leaf collection hose has a long reach of 4,2 m.
- Adjustable handle** An adjustable handle on the leaf suction hose makes it easy for the user to adjust the working position. The supporting arm prevents the hose from resting on and damaging hedges and ornamental plants during work.
- Central adjustment** Central adjustment of the casters ensures quick and easy adjustment of suction height, making sure that it fits both the surface and the amount of leaves perfectly.
- Two turbines** The two turbines, one in the leaf suction unit and one in the hopper, ensure that the leaves are finely chopped and ready for composting when they are collected in the hopper for leaf collecting. Hopper/grass collector is purchased separate.

Extra equipment (options):

- Grass collector** Must be combined with the grass collector hopper in order to function. Please see separate data for grass collector/hopper specifications and functions.

Technical specifications

Dimensions		
Length	mm	3100
Width	mm	1200
Height with cabin	mm	1950
Storage dimensions		
Length	mm	800
Width	mm	1050
Height	mm	900
Weights		
Weight with / without cabin ¹⁾	kg	995 / 885
Payload with / without cabin	kg	305 / 415
Weight (leaf suction unit)	kg	90
Performance		
Vacuum width	mm	1050
Ground clearance under vacuum nozzle	mm	180
Leaf collection hose reach	mm	4200
Suction hose diameter Ø	mm	125
Leaf collection hose diameter	mm	125
Airflow between 2 turbines	m³/h	2250
Airspeed in leaf collection hose	km/h	184
Operating speed	km/h	3-6
CE certified according to EU directive		

¹⁾ Includes: leaf suction unit, grass collector, 75 kg operator and 90% fuel capacity.



Tipping shovel

- Park Ranger 2150



1045 mm



2790 mm

1210 mm
1935 mm


Technical specifications

Dimensions		
Length	mm	2790
Width	mm	1045
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	670
Width	mm	1045
Height	mm	405
Weight		
Weight (tipping shovel)	kg	38
Performance		
Volume	l	66
Lifting capacity	kg	100
Ground clearance under shovel	mm	480
CE certified according to EU directive		



Tipper trailer

- Park Ranger 2150



Standard equipment:

- Steel chassis** The tipper trailer features a strongly built steel chassis with fixed headboard and sides.
- Hydraulic tip function** The unloading of the 0,44 m³ trailer is easily done via the joystick from the comfort of the driver seat.
- Support wheel** The support wheel allows for easy attaching, detaching and storage.

Extra equipment (options):

- Side extensions** The optional side extensions increase the volume of the trailer. The side extensions are 40 cm in the height.
- Lighting** The galvanized beam with rear lights makes the trailer visible in traffic.



Technical specifications

Dimensions		
Length	mm	4340
Width	mm	1025
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	2100
Width	mm	1025
Height	mm	850
Weight		
Weight (tipper trailer)	kg	160
Performance		
Platform, length	mm	1500
Platform, width	mm	950
Platform, height	mm	310
Platform, height with optional side extensions	mm	350
Volume	m ³	0,44
Volume with side extensions	m ³	1,02
Load carrying capacity, max.	kg	440
Loading height	mm	850
CE certified according to EU directive		



Load carrier with tip

- Park Ranger 2150



Standard equipment:

- Hydraulic tipping** The hydraulic tipping action makes it fast and easy to empty the load carrier with tip.
- Removable sides** The volume can be adjusted with the removable sides.
- Lockable back flap** The back flap can be locked in the horizontal position to allow for the transportation of planks, garden tools etc.
- Stand** The supplied stand allows for simple and quick fitting and removal of the load carrier with tip. One person can therefore easily attach / detach the load carrier with tip alone.

Technical specifications


Dimensions		
Length	mm	2440
Width	mm	1015
Height with / without cabin	mm	1935 / 1340
Storage dimensions		
Length	mm	1400
Width	mm	950
Height	mm	1350
Weights		
Weight with / without cabin ¹⁾	kg	770 / 660
Payload with / without cabin	kg	530 / 640
Weight (load carrier with tip)	kg	138
Performance		
Platform, length	mm	1040
Platform, width	mm	860
Platform, height	mm	300/600
Volume	m ³	0,4
Load carrying capacity, max.	kg	300
Loading height	mm	700-1040
CE certified according to EU directive		

¹⁾ Includes: load carrier, 75 kg operator and 90% fuel capacity.



Snow sweeper

- Park Ranger 2150



Standard equipment:

- Trapeze mounting** The trapeze-mounting ensures the snow sweeper remains clear of the wheels of the utility machine at all times, whatever the angle. The snow sweeper automatically turns with the utility machine - always sweeping in front of the wheels of the utility machine.
- Reverse rotation function** Reversing the brush rotation ensures that the operator can sweep material when reversing out of an alley or parking spot, which ensures an excellent result.
- Adjustable speed** The rotation speed can easily be adjusted from the cabin to match the need for sweeping.
- Support stand** A support stand with a wheel is build in to the snow sweeper for easy storage.

Extra equipment (options):

- Extended brush guard** Attaching a brush guard extends the snow sweeper cover, which minimises the snow whirling up on the front wind-screen. Furthermore, the guard makes it easier to control the direction of swept sand and gravel during summer operation. This can be retrofitted on existing snow sweepers as well.

Technical specifications

Dimensions		
Length	mm	3020
Width	mm	1220
Height with cabin	mm	1935
Storage dimensions		
Length	mm	900
Width	mm	1220
Height	mm	650
Weight		
Weight (snow sweeper)	kg	101
Performance		
Clearing width - straight	mm	1220
Clearing width - angled 25°	mm	1140
Ground clearance below brush	mm	420
Brush diameter Ø	mm	550
Operating speed	km/h	1-10
Theoretical sweeping capacity	m ² /h	12200
Handling snow depth up to	mm	150
Brush speed	rpm	255
Turning angle		25°
CE certified according to EU directive		



Snow blower

- Park Ranger 2150



Standard equipment:

- Adjustable chute** The snow blower has an adjustable chute that ejects snow 1-10 m away.
- Blade and skid** The snow blower has a replaceable blade and an adjustable skid.

Extra equipment (options):

- Counterweight** If the snow blower is being used without the salt and sand spreader we recommend the use of a counterweight for balancing.



Technical specifications

Dimensions		
Length	mm	2740
Width	mm	1015
Height with cabin	mm	1935
Storage dimensions		
Length	mm	790
Width	mm	1010
Height	mm	1050
Weight		
Weight (snow blower)	kg	120
Performance		
Clearing width	mm	1000
Feed intake height	mm	600
Ground clearance below snow blower	mm	420
Auger diameter	mm	380
Ejection chute diameter	mm	380
Axle revolutions per minute	rpm	950-1300
CE certified according to EU directive		



Snow plough

- Park Ranger 2150



Standard equipment:

- Safety tilt system** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function reduces the risk of damages both to the plough and surroundings.
- Rubber scraper edge** 100 mm high, 26 mm thick and 1300 mm wide rubber scraper. The scraper edge can be used on two sides giving double usage and extended lifetime.

The rubber scraping edge is ideal for use with melting snow and also scrapes the surface thoroughly without damaging it.
- Floating skids** The 2 skids are hight adjustable and ensures that the blade follows ground variations.


Technical specifications

Dimensions		
Length	mm	2700
Width	mm	1300
Height with cabin	mm	1935
Storage dimensions		
Length	mm	550
Width	mm	1300
Height	mm	545
Weight		
Weight (snow plough)	kg	67
Performance		
Clearing width - straight	mm	1300
Clearing width - inclined	mm	1130
Ground clearance below scraper	mm	400
Ground clearance under support strut	mm	350
Operating speed	km/h	1-16
Handling snow depth up to	mm	350
Turning angle		30°
Theoretical performance	m ² /h	20800
CE certified according to EU directive		



Snow V-plough

- Park Ranger 2150



Standard equipment:

Hydraulic angle adjustment	Each side/blade can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blades when needed.
Vibration damping	A-frame featuring integrated vibration damping, which increases comfort and reduces noise.
Vulkollan scraper edge	The vulcanised rubber scraping edge is good for surfaces that require extra care. The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either vulcanised rubber scraper or steel scraper.
Steel scraper edge	The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either steel scraper or vulcanised rubber scraper.
Safety tilt function	When operating in deep snow there is a risk of hitting obstacles. The safety tilt function of lower part of the V-plough reduces the risk of damages both to the plough and surroundings.
Floating skids	The 2 skids are height adjustable and ensures that the plough follows ground variations.


Technical specifications

Dimensions		
Length	mm	2700
Width (straight)	mm	1400
Height with cabin	mm	1935
Storage dimensions		
Length	mm	500
Width	mm	1200
Height	mm	600
Weight		
Weight (snow V-plough)	kg	114
Performance		
Clearing width - straight	mm	1400
Clearing width - inclined	mm	1200-1400
Clearing width - 30°, Y- & V-form	mm	1200
Ground clearance below scraper	mm	140
Ground clearance under support strut	mm	125
Operating speed	km/h	1-16
Handling snow depth up to	mm	500
Turning angle		30°
Theoretical performance	m ² /h	22400
CE certified according to EU directive		



Salt and sand spreader

- Park Ranger 2150



Standard equipment:

Durable material	All parts that get in contact with salt and sand are rust free, made of synthetic material or stainless steel.
Stirrer	The stirrer prevents blocking, crushes lumps and ensures precise and uniform spreading - and thereby even thawing of the ground. Made of hardened Hardox steel the stirrer fingers are extremely robust.
Material storage	There is space for extra bags of salt and sand on top of the hopper grate, enabling the operator to fill the salt and sand spreader on site. Please note the maximum loading capacity.
Stand	A stand for attaching/detaching is delivered with the spreader as standard. The stand has wheels, making it easy to move the spreader into storage without heavy lifting.
Tarpaulin cover	A cover keeps the material dry and thereby indirectly improve the spreading accuracy.

Extra equipment (options):

Auger cover for vacuum salt	The cover ensures that tiny material such as vacuum salt, does not just run out of the spreader, which reduces the waste and increase the operation efficiency.
------------------------------------	---

Technical specifications

Dimensions		
Length	mm	2510
Width	mm	1015
Height with cabin	mm	1935
Storage dimensions		
Length with stand	mm	1175
Width	mm	800
Height with stand	mm	1350
Weights		
Weight with cabin ¹⁾	kg	860
Payload with cabin	kg	440
Weight (spreader)	kg	97
Weight of stand	kg	31
Spreader		
Volume	l	210
Spreader load, max.	kg	350
Loading height	mm	1250
Performance		
Spreading width	mm	1000-5000
Operating speed	km/h	1-16
CE certified according to EU directive		

¹⁾ Includes: salt and sand spreader, 75 kg operator and 90% fuel capacity.



Honest Work.

Egholm A/S develops, produces and markets utility machines that keep roads, parks and outdoor areas clean and inviting all year round. We supply functional quality machines and attachments to people who do an honest day's work keeping our cities clean and attractive. With special attachments developed for the machines, Egholm machines deliver perfect results no matter the task at hand. Built by craftsmen in Denmark, Egholm machines are in operation in cities and parks all over the world.

Honest Machines.

Egholm utility machines are developed by people who are passionate about technology and innovation. We listen to the people driving, using and servicing Egholm machines, because they are the true experts. It is our mission to design, build and market utility machines that deliver perfect results in real life. Egholm machines are honest machines - not just because they deliver comfort, safety and strong end results: They are also a sound investment for years to come and give you outstanding return on your investment.

Honest People.

We want you to think of us as your partner in every single way. And we always insist on reliability, trust and honesty in our partnership with you and with our network of dealers and service partners. We are straightforward and direct in our communication and in our dealings with everyone. Our belief in hard work and unwillingness to compromise helps us deliver the quality for which we are known. And we believe it is reflected by the machines we build for you, as well.

Egholm A/S

Transportvej 27
7620 Lemvig, Denmark
T.: +45 97 81 12 05
www.egholm.eu - info@egholm.dk

Egholm GmbH

Am Hafen 24
38112 Braunschweig, Germany
T.: +49 (0) 531 129 77-0
www.egholm.de - info@egholm.de